



## **RAS-570**

### **Automatic Two-Piece Eyeleted Hangtag Threading Machine**

#### **Application:**

This machine is designed for the market's eyelet stringing tag and two-tags-at-the-same-time stringing products.

The 570 is capable of automatic punching, attaching eyelets, matching tags, stringing, knotting, and counting at one time. It is specially designed to perforate a hole, perforate the eyelet, and thread two tags of different sizes simultaneously, also for a single tag.

# ROYO MACHINERY

## Technical parameters:

	AS-350	AS-570	AS-570H
Speed:	2000-5000pcs/h	2000-5000pcs/h	2000-5000pcs/h
Max size of hangtag:	80*135mm	80*135mm	80*135mm
Min size of hangtag:	22*50mm	22*50mm	22*50mm
Standard size of hole diameter:	4.2mm (Can replace the punch mould)		
Diameter of string:	Standard: 0.3-2.1mm Silk ribbon width: ≤4mm Elastic string: 0.3-1.5mm		
Length of string:	80-180mm, silk ribbon width: ≥11.5mm		
Length of tail of string:	15-20mm	15-20mm	15-20mm
Thickness of hangtag:	180g-1200g		
Hole size of hangtag:	≥3mm	≥3mm	≥3mm
Machine size:	1140mm*1350mm*1360mm	1140mm*1350mm*1360mm	1140mm*1350mm*1360mm
Machine weight:	1000KG	1200KG	1200KG
Voltage:	3phase 380V	3phase 380V	3phase 380V
Power:	1620W	1620W	1620W

Pictures and parameters are only for reference.

Modified:

AS-570H Cold & Hot Cutting

RF-910 Automatic Three Pieces Hangtags Gathering and Threading Machine



**RSCG-160T**

## **Automatic Hangtag Threading Machine**

### **Application:**

This universal automatic hangtag threader machine was specifically designed for European and American popular threaded hangtags and hang cards for the local market. This machine can punch, thread, tie, and count at one time all kinds of ropes, ribbons, and elastic strings. This machine makes little noise and is easy to use. The debugging and maintenance of the 160T is simple and convenient, which is necessary for efficient and speedy hangtag production.

# ROYO MACHINERY

## Technical parameters:

	<b>RSCG-160T</b>	<b>RSCG-160E</b>	<b>RSCG-180H</b>
Speed:	1000-6000pcs/h	1000-6000pcs/h	1000-6000pcs/h
Max size of hangtag:	95*150mm	95*150mm	95*150mm
Min size of hangtag:	20*40mm	20*40mm	20*40mm
Standard size of hole diameter:		3.2mm, 4.2mm (Can replace the punch mould)	
Diameter of string:	Standard: 0.3-2.1mm Silk ribbon width: ≤6mm Elastic string: ≤1.5mm	Standard: 0.3-2.1mm Silk ribbon width: ≤6mm Elastic string: ≤1.5mm	Standard: 0.3-2.1mm Silk ribbon width: ≤6mm Non-elastic string
Length of string:		90-180mm, silk ribbon width: ≥11.5mm	
Length of tail of string:	15-20mm	15-20mm	15-20mm
Thickness of hangtag:		157-700g (Modified mould for out limit thickness)	
Machine size:	1100mm*1100mm* 1200mm	1100mm*1100mm* 1200mm	1100mm*1100mm* 1200mm
Machine weight:	650KG	650KG	650KG
Voltage:	3phase 380V	3phase 380V	3phase 380V
Power:	750W	750W	750W

Modified:

RSCG-180H Automatic Hangtag Cold & Hot Cutting Threading Machine